


Spectroelectrochemical Transmission Cell

A versatile, thin-layer optically-transparent electrode transmission cell for in-situ FTIR
Spectroelectrochemical analysis from -50°C to 70°C.



Spectroelectrochemical Transmission Cell

Spectroelectrochemistry couples the techniques of electrochemistry and spectroscopy. It involves the application of an electric field to a sample whilst simultaneously recording spectroscopic absorption features, and has particular application for monitoring redox-coupled reactions to allow in-situ spectroscopic analysis of electro-generated intermediates and/or products.

The Specac Spectroelectrochemical transmission cell is an FTIR accessory encompassing a thin-layer optically-transparent electrode structure to facilitate electrochemical spectroscopic measurements.

The cell comprises two CaF₂ windows separated by a 100 or 200 micron sample layer, where gold grid working and counter electrodes, and a silver reference electrode, are photolithographically imprinted on the surface of the front window in contact

with the sample. Grid structures with a period of 20 lines/mm are available as standard. Perfluoroelastomer seals are used to ensure chemical compatibility with a range of organic solvents, and the demountable cell design allows for ease of cleaning. The cell is air-tight, has a small sample volume (ca 0.3 – 0.6 ml), and can be used in an evacuated environment.

Specac's Spectroelectrochemical transmission cell follows a modular design concept to fit with a range of Specac sample holders. In particular, the cell is compatible with Specac's Standard Cell Holder, Variable Temperature Cell holder, Water Heating/Cooling jacket, and Electrical Heating jacket, to allow Spectroelectrochemical transmission measurements from - 50°C to 70°C.

Ordering Information

GS20900 Spectroelectrochemical Transmission Cell

Note: This cell includes both 100 micron and 200 micron spacer options, and is shipped configured at 200 microns

.....

Key Features & Benefits

- Demountable cell design for ease of cleaning
- Modular design to fit a range of sample holders to facilitate operation from -50°C to 70°C
- Gold working and counter electrodes imprinted on cell window
- Perfluoroelastomer seals to ensure compatibility with a range of solvents
- Calcium fluoride windows for UV and IR applications
- 100 and 200 micron optical pathlengths

Cell Holders (one required)

GS20740	Sample Cell ambient temperature holder with 3" x 2" backplate mount
GS20710	Water Heating Jacket
GS20730	Electrically Heated Jacket + temperature controller*
GS21525	Variable Temperature Cell + temperature controller**

*Notes: *specify country; **Includes NaCl windows (pair) for jacket; must specify country for controller power cables and spectrometer for baseplate*

Associated and replacement parts

GS20907	Pair of external perfluoroelastomer seals
GS20908	Pair of internal perfluoroelastomer seals
GS20909	Rear CaF ₂ window
GS20910	Front CaF ₂ window (with electrode)
GS20980	Variable Temperature Cell flow fittings kit
GS20200	Variable Temperature Cell spare thermocouple (T-type Copper/CopperNickel)
GS20802	Variable Temperature Cell replacement CaF ₂ windows (pair) for jacket

SPECAC LTD.,
River House, 97 Cray Ave, St. Mary Cray, Orpington,
Kent, BR5 4HE UK
T : +44 (0)1689 873134 F : +44 (0)1689 878527
E : sales@specac.co.uk Registered in England No. 1008689

SPECAC INC.,
50 Sharpe Drive, Cranston, RI 02920 USA
T : Toll Free +1 800 447 2558
E : sales@specac.com W : www.specac.com
Specac is part of Smiths Group plc

44 - 02/10